




METALES Y PERFILES
S.A.

RIELES FICHA TECNICA.

PESO NOMINAL POR YARDA	TIPO DE RIEL	DIMENSIONES EN PULGADAS								SECCIÓN DE DESIGNACION		
		HT	BW	HW	W	HD	FD	BD	E			
12 lb.	ASCE	2	2	1	3/16	9/16	1-3/32	11/32	57/64	1240	12 AS	-
16 lb.	ASCE	2-3/8	2-3/8	1-11/64	7/32	41/64	1-23/64	3/8	1-1/16	1640	16 AS	-
20 lb.	ASCE	2-5/8	2-5/8	1-11/32	1/4	23/32	1-15/32	7/16	1-11/64	2040	20 AS	-
25 lb.	ASCE	2-3/4	2-3/4	1-1/2	19/64	25/32	1-31/64	31/64	1-15/64	2540	25 AS	-
30 lb.	ASCE	3-1/8	3-1/8	1-11/16	61/64	7/8	1-23/32	17/32	1-25/64	3040	30 AS	-
35 lb.	ASCE	3-5/16	3-5/16	1-3/4	23/64	61/64	1-25/32	37/64	1-15/32	3540	35 AS	-
40 lb.	ASCE	3-1/2	3-1/2	1-7/8	25/64	1-1/64	1-55/64	5/8	1-9/16	4040	40 AS	-
45 lb.	ASCE	3-11/16	3-11/16	2	27/64	1-1/16	1-31/32	21/32	1-41/64	4540	45 AS	-
50 lb.	ASCE	3-7/8	3-7/8	2-1/8	7/16	1-1/8	2-1/16	11/16	1-23/32	5040	50 AS	-
55 lb.	ASCE	4-1/16	4-1/16	2-1/4	15/32	1-11/64	2-11/64	23/32	1-103/128	5540	55 AS	-
56 lb.	MISC.	4	3-27/32	2-5/16	11/32	1-13/32	1-29/32	11/16	1-41/64	5607		
	MISC.	4-1/4	4-1/8	2-1/4	3/8	1-27/64	2-1/8	45/64	1-3/4	5633	56-M	5616
60 lb.	ASCE	4-1/4	4-1/4	2-3/8	31/64	1-7/32	2-17/64	49/64	1-29/32	6040	60 AS	603
	ARA-A	4-1/2	4	2-1/4	15/32	1-15/64	2-29/64	13/16	2-17/64	6020	60 RA	602
	MISC.	4-1/4	4-1/16	2-5/16	1/2		2-1/8			6001		6051
65 lb.	ASCE	4-7/16	4-7/16	2-13/32	1/2	1-9/32	2-3/8	25/32	1-31/32	6540	65 AS	653
70 lb.	ASCE	4-5/8	4-5/8	2-7/16	33/64	1-11/32	2-15/32	13/16	2-3/64	7040	70 AS	701
72 lb.	C&NW	4-3/4	4-3/4	2-3/8	9/16	1-12/32	2-1/2	27/32	2-3/32	7201	72 NP	7250
75 lb.	ASCE	4-13/16	4-13/16	2-15/32	17/32	1-27/64	2-35/64	27/32	2-15/128	7540	75 AS	753
	MO. PAC.	4-3/4	4-3/4	2-9/16	9/16	1-7/16	2-15/32	27/32	2-5/64	7550	75 MP	-
	S. PAC.	4-15/16	4-7/16	2-7/16	33/64	1-3/8	2-5/8	15/16	2-1/4	7524	75 SP	754
	U. PAC.	5	5	2-9/16	1/2	1-3/8	2-13/16	13/16	2-5/8	7523	75 CS	754
	U. PAC.	4-15/16	4-7/16	2-7/16	33/64	1-3/8	2-5/8	15/16	2-1/2	7524	75 CSR	757
80 lb.	ASCE	5	5	2-1/2	35/64	1-1/2	2-5/8	7/8	2-3/16	8040	80 AS	800
	DUDLEY	5-1/8	5	2-21/32	17/32	1-1/2	2-3/4	7/8	2-1/4	8022	80 DY	-
85 lb.	ASCE	5-3/16	5-3/16	2-9/16	9/16	1-35/64	2-3/4	57/64	2-17/64	8540	85 AS	851
	CAN. PAC.	5-1/8	5	2-1/2	9/16	1-7/16	2-11/16	1	2-11/32	8524	85 CP	-
	CB&Q	5-3/16	5-3/16	2-21/32	9/16	1-35/64	2-3/4	57/64	2-17/64	8543	85 CB	852
	GRT. NO.	5	5	2-21/32	21/32	1-19/32	2-1/2	29/32	2-5/32	8509	85 GN	8553
	MO. PAC	5-7/32	5-1/4	2-15/32	75/128	1-3/4	2-39/64	55/64	2-21/128	8550	-	-
	PS	5-1/8	4-5/8	2-1/2	17/32	1-21/32	2-15/32	1	2-15/64	8531	85 PS	-
	PRR	5	5	2-9/16	17/32	1-3/4	2-3/8	7/8	2-1/16	8533	85 PR	-
	SOO LINE	5-3/8	4-7/8	2-1/2	9/16	1-15/32	2-29/32	1	2-29/64	8520	-	-
90 lb.	ASCE	5-3/8	5-3/8	2-5/8	9/16	1-35/64	2-55/64	59/64	2-45/128	9040	90 AS	-
	ARA-A	5-5/8	5-1/8	2-9/16	9/16	1-15/32	3-5/32	1	2-37/64	9020	90 RA	902
	ARA-B	5-17/64	4-49/64	2-9/16	9/16	1-39/64	2-5/8	1-1/32	2-11/32	9030	90 RB	905
	AT&SF	5-5/8	5-3/16	2-9/16	9/16	1-15/32	3-5/32	1	2-37/64	9021	90 SF	903
	C&NW	5-17/32	5-3/32	2-1/2	1/2	1-17/32	2-31/32	1-1/32	2-23/64	9035	90 OM	-
	D&RG	5-1/2	5-1/8	2-9/16	9/16	1-5/8	2-7/8	1	2-5/8	-	-	906
	GRT. NO	5-3/8	5	2-5/8	9/16	1-15/32	2-7/8	1-1/32	2-15/32	9024	90 GN	904
	INTRBGH	5	5	2-7/8	11/16	1-25/32	2-11/32	7/8	2-3/64	9050	90 RT	-
	U. PAC.	5-3/4	5-3/8	2-3/4	17/32	1-1/2	3-3/8	7/8	2-9/16	9023	90 UP	901
	DUDLEY	5-1/2	5	2-21/32	9/16	1-1/2	3-1/32	31/32	2-3/8	-	90 DY	-



Dimensiones de la Tabla de Datos

HT - ALTURA
 BW - ANCHO DE LA BASE
 HW - ANCHO DE LA CABEZA
 W - ESPESOR VENA
 HD - LA PROFUNDIDAD DE LA CABEZA
 FD - ALTURA MEDIA
 BD - LA PROFUNDIDAD DE LA BASE
 E - AGUJERO PASANTE ELEVACION